
Annual CRMC Performance Driving School PRE-EVENT TECHNICAL INSPECTION FORM



Make	Model:	Year:
understand that the condition	on of my car is my responsibility, and	d the technical inspector is not responsible for any potential failure of my car.
vehicle. I release, acquit, an business, their officers, mem	d forever discharge the organizers, obers, contractors, lessors, associate	RMC) and the Open Track Staff hold me/us responsible for the condition of thic Carolina Motorsports Park, CRMC, the Open Track Staff and any sponsoring es, successors or assigns from any and all liability, claims for damages or cauchehicle, whether or not due to negligence.
Date: Drive	er/Owner Print:	Sign:
Date:2nd D	Oriver Print:	Sign:
For 16 & 17 year old stude	nts:	
Date:Pare	nt/Guardian Print:	Sign:
Inspecting Service Sh	юр:	Date:
	Complete all lines with before	
Exterior Brake lights: all work	ina	Hub caps & beauty rings removed
	specs or adjusted for track condition	
All lug nuts present &		Front & rear glass clean, unobstructed, no major cracks
	aks; gas, oil, coolant, brake fluid.	Gas cap tight or taped shut
Tires less then 5 years o		Mirrors: Left-hand exterior & windshield rear view required
Engine Compartment and		<u> </u>
		Cameras, gauges, g-analyst, etc. mounted securely
		Brake fluid: fluid fresh, proper level, system bled
Throttle linkage: not stic		Date of last brake fluid change/
	level, hoses good, clamps tight	-
Radiator cap holds pres		Engine belts: properly tightened, not frayed or cracked
Under Car – on lift or jack		
	oad thickness (Minimum 5mm, cons	ider bringing extras if not new)
	•	Calipers, hoses & lines: clean, dry & working properly
		Wheels: straight, not damaged, no cracks
Steering linkage: No excessive play		Suspension: no excessive play, no cracks/bad rust in mounts
Check transmission and	· ·	Check rear engine, transmission seals for excessive seepage
	_	Exhaust: no under car leaks. All clamps and hardware tight
	-shaft bolts for looseness	
— Safety Equipment & Rules		
Front seat belts: prop		used with harness bar, roll bar or roll cage, minimum 5 point required.
Roll bar: Minimum 4-	point mounting. Adequate padding	required on
oar/cage at any possible cor	ntact point with driver's or passenge	r's head.
No Nitrous or other for	uel enhancements allowed.	
At Track Only Helmet: S	Snell SA2015 or SA2020 with Snell s	sticker inside. Absolutely required to get on the track.
At Track Only Clothing:	Long pants and long or short sleeve	e shirt of natural fibers, closed-toed shoes required.